

GLQ2471MOH 2.4/5/6 GHz 4/4/5 dBi Omni Antenna

MODEL GLQ2471MOH

Tri-band omni antenna covering 2400-2500, 5150-5950 and 6000-7125 MHz for 2.4/5/6G WLAN systems, supporting IEEE 802.11a/b/g/n.



KEY PERFORMANCE

2400-2500 / 5150-5950 / 6000-7125 MHz

FREQUENCY RANGE

4 / 4 / 5 dBi *

PEAK GAIN

<= 2.0

VSWR

4 x RPSMA male

CONNECTOR

TECHNICAL SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Frequency band	2400-2500 / 5150-5950 / 6000-7125 MHz
Polarization	Vertical
Peak gain *	4 / 4 / 5 dBi
VSWR	<= 2.0
Isolation	>= 13 / >= 20 / >= 20 dB
Impedance	50 ohm
Max. power	50 W

MECHANICAL SPECIFICATIONS

Connector type	4 x RPSMA male
Connector position	Bottom
Exposed cable	1220±10 mm (or user's customization)
Radome material	PC
Radome color	White
Dimensions	Dia. 90 x 40 mm
Weight	180 g
Operating temperature	-40°C to +85°C
Operating humidity	5-95%
Mounting type	Fixed with nut

NOTES

* Gain measured with 18 inch cable. Values are taken from the source specification table.

GLOBAL RF TECH

Zhengzhou LEHENG Electronic Technology Co., Ltd.
<https://globalrftech.com/> | Email Sales | Call Us

NEED A CUSTOM CONFIGURATION?

Frequency, connector, cable length and mounting options can be reviewed for your project.
[Request a quote](#)